

















































































Color Variation











Member



Member of Canada Green Building Council



Member of U.S. Green Building Council



The Terrazzo, Tile, and Marble Association of Canada



America (CTDA)

Marble Institute Distributors of of America

For information concerning LEED, please contact our Sales Representative

Packing Details

TILE SIZE	PC/BOX	SF/BOX	LB/BOX	BOX/PAL
7" x 48" with underpad Matte	11	26.19	43.45	55

Examples of Recommended **Applications**













The Chimewood Collection is our signature luxury vinyl tile flooring that features authentic design, natural color, and realistic texture that recreates the beauty of real hardwood.

The collection is Floorscore certified for low VOC providing an environmentally friendly option for flooring applications both commercial and residential.

The collection features a hinge to ensure a seamless water proof installation.

Maintenace Guide for SPC Flooring

- Regularly sweep the floor to remove loose dirt or grit as these can cause fine scratches.
- For a thorough clean, a range of pH neutral cleaning products are available. Avoid the use of regular household cleaners and bleach-based detergents. These could make the floor slippery or cause discoloration.
- · Always mop up spills as soon as possible, to reduce the risk of slipping and possible staining.
- · Use entrance mats to protect against grit and moisture. Ensure they are of non-staining variety (not rubber-backed) to prevent any discolouration of the floor.
- · Avoid sliding or dragging furniture or other objects across the floor use floor protector pads to prevent scratching.
- Use large castor cups or other means to protect against indentation from heavy furniture.
- Maintain room temperature between 65-85°F* (18-27°C) for optimum performance.
- Do not subject this product to standing water. This this will present a slip hazard.
- · Care must be taken when using underfloor heating to avoid damage to the floor caused by localised 'hot spots/thermal blocks'. Care must also be taken in placing rugs, and items of furniture which do not allow hot air circulation.

ASTM standards require installation in range 65-85°F; elsewhere the temperature should be 18-27°C.

** Where the flooring run exceeds 50 ft. (15 m) in width or length, a 5/16" (8 mm) expansion joint should be used and repeated thereafter.

alphatile & stone 🗏

Tampa

2443 East Meadow Blvd Tampa, FL 33619 (813) 620-9000 (800) 785-9000

Fort Myers

10898-A Metro Parkway Ft. Myers, FL 33966 (239) 275-8288 (800) 785-8288

Sarasota

1808 Whitfield Ave. Sarasota, FL 34243 (941) 727-7433 (800) 785-3484











