

alphatile & stone #

BIANCO



12 x 24 UI.LD.BIA.1224

BEIGE



12 x 24 UI.LD.BGE.1224

All items shown in this document are a part of Alpha's stocking program. For special orders please contact your Alpha Tile Sales Representative

GRIGIO (GREY)



12 x 24 UI.LD.GRG.1224

ANTHRACITE



12 x 24 UI.LD.ATR.1224

All items shown in this document are a part of Alpha's stocking program. For special orders please contact your Alpha Tile Sales Representative

Packing Information

TILE SIZE	PC/BOX	SF/BOX	LB/BOX	BOX/PALLET
12x24	8	16.06	52	60

Test Performed -- Results Conform

Water Absorption	ISO 10545-3	≤0.5% (porcelain) ≤3.0% (monocottura)	0.321
DCOF	ANSI A137.1/2012	≥0.42	
	DIN 51130/51097	R9	R9
Slip Resistance	BCR	≤.40 to ≤.74	
Bending /	ISO 10545-4	>1300N / >35N/mm² (porcelain) >1000N (monocottura)	1300N
Breaking Strength	ASTM-C648	≥ 250 lbs	255.528
Deep Abrasion	ISO 10545-6	1753	
Resistance	ASTM C-1243	≤ 175 mm³	
Chemical	ISO 10545-13	≥UB	Not Affected
Resistance		GA / GLA	
Stain Resistance	ISO 10545-14	> Class 3	Not Affected
	ISO 10545-12	ia Ža	Yes
Frost Resistance	ASTM C-1026	n/a	
DEL Dating	ISO 10545-7		PEI 4
PEI Rating	ASTM C-1027	III a	FE14
Scratch Hardness	MOHs	n/a	N/A
Variation Rating	n/a	n/a	V-1

Technical Data in provided by the manufacturer and is subject to change at any time. Olympia does not provide warranties as to the specifications of any product.

Color Variation:

V2 V3 V4

Member:











Recommended Uses:



















ANTHRACITE



GRIGIO (GREY)